

### US-35140-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

### **CB TEST CERTIFICATE**

Product POWER SUPPLY

Name and address of the applicant SL POWER ELECTRONICS CORP

BLDG A 6050 KING DR VENTURA CA 93003 UNITED STATES

Name and address of the manufacturer SL POWER ELECTRONICS CORP

BLDG A 6050 KING DR VENTURA CA 93003 UNITED STATES

Name and address of the factory SL XIANGHE POWER ELECTRONICS CORP

NO.B-02-03,NORTH SIDE OF LANDSCAPE AVE, QIBU DISTRICT, ENVIRONMENTAL INDUSTRIAL PARK XIANGHE

HEBEI 065400 CHINA

Additional Information on page 2

Ratings and principal characteristics See Page 2

SL

Trademark / Brand (if any)

Note: When more than one factory, please report on page 2

Model / Type Ref. NGB425SXXKZZ
See Page 2

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

E511363-A6003-CB-2 issued on 2020-01-16

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2020-01-19 Signature:

Jolanta M. Wroblewska



### US-35140-UL

# Model Details:

NGB425SXXKZZ

Where XX represents the output voltage which may be any number from 12 to 48. ZZ can be any number between 00-99, blank or any letter from AA to ZZ, only for market purpose, not influence safety function.

#### Factories:

INDUSTRIAS S L S A DE C V

CIRCUITO SIGLO XXI 2055 COL PARQUE INDUSTRIAL EX-XXI 21254 MEXICALI BC

**MEXICO** 

## Ratings:

Input:

100-240 Vac, 50-60 Hz, 5.5A

Output:

Model NGB425S12K For convection: Output1: 12Vdc/19.5A Output2: 5Vdc/0.5A

For 400LFM:

Output1:12Vdc/30.0A Max. Output2: 5Vdc/1A Max. Model NGB425S15K For convection:

Output1: 15Vdc/13.17A Output2: 5Vdc/0.5A

For 400LFM: Output1: 15Vdc/24.0A Max.

Output2: 5Vdc/1A Max.

Model NGB425S24K
For convection:
Output1: 24Vdc/11.15A
Output2: 5Vdc/0.5A
For 400LFM:

Output1: 24Vdc/17.5A Max. Output2: 5Vdc/1A Max. Model NGB425S48K For convection: Output1: 48Vdc/5.57A Output2: 5Vdc/0.5A For 400LFM:

Output1: 48Vdc/8.75A Max. Output2: 5Vdc/1A Max.

#### Additional Information:

Additionally evaluated to EN 62368-1:2014/A11:2017. National Differences specified in the CB Test Report.

## **Additional information (if necessary)**



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2020-01-19

Signature:

Jolanta M. Wroblewska