

US-35908-UL

# IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## **CB TEST CERTIFICATE**

Product Name and address of the applicant	Switching Power Supply
Name and address of the applicant	
	SL POWER ELECTRONICS CORP BLDG A 6050 KING DR VENTURA CA 93003 UNITED STATES
Name and address of the manufacturer	SL POWER ELECTRONICS CORP BLDG A 6050 KING DR VENTURA CA 93003 UNITED STATES
Name and address of the factory	SL XIANGHE POWER ELECTRONICS CORP NO.B-02-03,NORTH SIDE OF LANDSCAPE AVE,
Note: When more than one factory, please report on page 2	QIBU DISTRICT, ENVIRONMENTAL INDUSTRIAL PARK XIANGHE HEBEI 065400 CHINA
	Additional Information on page 2
Ratings and principal characteristics	See Page 2
Trademark / Brand (if any)	SL Power
Type of Customer's Testing Facility (CTF) Stage used	OTE Stogo 2
Type of Customer's Testing Facility (CTF) Stage used	CTF Stage 3
Model / Type Ref.	1) CINT1175VXXYYKZZ, CINT1175A4806K02, 2) CINT1175A4806K03 See Page 2
Additional information (if necessary may also be reported on page 2)	Additionally evaluated to EN 62368-1:2014 / A11:2017; National Differences specified in the CB Test Report.
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	E135803-A6009-CB-1 issued on 2020-06-05

This CB Test Certificate is issued by the National Certification Body





Ref. Certif. No.

## US-35908-UL

#### Model Details:

CINT1175VXXYYKZZ, where V is A or B, where XX is any number 12 through 56, where YY or ZZ is any number 00 through 99.

Factories: INDUSTRIAS S L S A DE C V CIRCUITO SIGLO XXI 2055 COL PARQUE INDUSTRIAL EX-XXI 21254 MEXICALI BC MEXICO

Ratings: 1) Input: 100-240V~, 50-60Hz, 2.0A Output: Without Fan: Mainboard output: 12V, 10A MAX to 56V, 2.15 A, MAX. 120 W With Fan (200 LFM): Mainboard output: 12V, 14.6A MAX to 56V, 3.13A MAX Fan board output: 12VFAN, 0.4 A, MAX

For CINT1175A4806K02: + 48V, 1.25A MAX, 60 W with convection 2) Input: 100-277Vac, 50-60Hz, 2.0A Output: +48V 3.6A MAX and 12VFAN 0.4A MAX for fan with 200 LFM airflow; +48V 2.5A MAX with convection

### Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Jolanda / h. Wie

Signature: Jolanta M. Wroblewska

Date: 2020-06-05

2/2